Video & Air-Cushioned Light Stands

Studio and location support for professional video lighting.

TMY PROFESSIONAL DATASHEET / MODEL SPECIFICATIONS

TMY3000B



Min Height	1015mm
Max Height	3085mm
Closed Length	900mm
Net Weight	2.52kg
Sections	4
Tube Dia.	20, 25, 30, 35
Leg	22
Load Capacity	5kg
Packing	4pcs
Footprint	1070mm
Caster	—

TMY3000S



Min Height	1215mm
Max Height	2855mm
Closed Length	1040mm
Net Weight	4.20kg
Sections	3
Tube Dia.	25, 30, 35
Leg	20x20
Load Capacity	10kg
Packing	2pcs
Footprint	1180mm
Caster	3 in

TMZ3500



Min Height	1390mm
Max Height	3480mm
Closed Length	1220mm
Net Weight	4.0kg
Sections	4
Tube Dia.	25, 30, 35, 40
Leg	25
Load Capacity	5kg
Packing	4pcs
Footprint	1200mm
Caster	—

TMY3800LP



Min Height	1300mm / 51 in
Max Height	3800mm / 150 in
Closed Length	1150mm / 45 in
Net Weight	3.28kg
Sections	4
Tube Dia.	20, 25, 30, 35
Leg	22mm
Load Capacity	8kg / 17.68lbs
Packing	4pcs
Footprint	1200mm / 47.2 in
Caster	—

Video & Air-Cushioned Light Stands

Studio and location support for professional video lighting.

TMY PROFESSIONAL DATASHEET / MODEL SPECIFICATIONS

TMY3800TP



Min Height	**1300mm / 51 in**
Max Height	**3800mm / 150 in**
Closed Length	**1135mm / 45 in**
Net Weight	**2.90kg / 6.5lbs**
Sections	**4**
Tube Dia.	**20, 25, 30, 35**
Leg	**22mm**
Load Capacity	**8kg / 17.68lbs**
Packing	**4pcs**
Footprint	**1200mm / 47.2 in**
Caster	**—**

TMY3960FP



Min Height	**1300mm / 51 in**
Max Height	**3960mm / 160 in**
Closed Length	**1140mm / 45 in**
Net Weight	**2.94kg / 6.5lbs**
Sections	**4**
Tube Dia.	**20, 25, 30, 35**
Leg	**22mm**
Load Capacity	**8kg / 17.68lbs**
Packing	**4pcs**
Footprint	**1200mm / 47.2 in**
Caster	**—**

TMY SERIES — Video & Air-Cushioned Light Stands

Series positioning

The FENIGAL / BTCOOPS TMY Series is positioned as video & air-cushioned light stands for professional purchasing programs. Video-oriented telescopic stands include models with cushioning and caster variants. Model-level dimensions, nominal loads and options are documented on the preceding technical pages; choose the exact SKU rather than relying on a family-wide capability claim.

Primary search keywords

video light stand | air cushioned professional light stand | studio support tripod

Target B2B markets

broadcast; film and video; studio rental

Typical buyer personas

broadcast buyer; video equipment distributor; studio technician

Application scenarios

Studio key/fill lighting; location video shoots; temporary indoor event illumination; trade-show fixtures when the hardware is compatible.

Balloon-light system integration

BTCOOPS balloon-light integrators may evaluate this series only after a specific fixture, mounting and wind-load review. No universal balloon-light compatibility is claimed.

Buyer qualification / quotation checklist

Request the exact model code, equipment and accessory mass, installed working height, interface dimensions, ground/site conditions, intended duty cycle and quantities. Where relevant also identify boom outreach, mobility requirements, load offset, weather and mounting accessories.

Frequently Asked Questions

What information is needed to select a stand?

Share the fixture weight including cables and accessories, target mounting height, attachment dimensions, intended location and whether the setup is static or frequently moved. Compare the exact model specifications.

Can these supports carry BTCOOPS balloon lights?

Potential suitability must be assessed model by model. A balloon fixture can impose additional overturning loads; confirm the balloon diameter, complete assembled mass, center of gravity, mount interface, approved support and any wind restrictions with BTCOOPS before purchase.

Can the stand be used outdoors?

An outdoor application is possible only after a site-specific review of levelness, wind exposure, anchoring, ballast and fixture instructions. Catalog payload alone is not a wind rating.

How should buyers interpret the listed load capacity?

It is a catalog-supplied nominal load value, not an independent certification, wind-load rating or guarantee for offset/boom configurations. Request the factory rating conditions for critical applications.

What should be confirmed before an OEM or wholesale order?

Confirm the exact SKU, finish, folded dimension, transport packaging, top spigot/thread, required adapters, quantity, customization and factory-approved loading conditions.

Technical and publication notes

Specifications and product images on the preceding pages are taken from the user-provided supplier catalog. Application positioning and buyer personas are marketing recommendations; no additional test results, certifications, IP ratings, wind resistance or mounting compatibility are asserted. Confirm claims with the manufacturer before publication.

www.btcoops.com |