Low Roller Bases & Wheeled Riser Stands

Mobile low-position support and adjustable risers for professional lighting setups.

TX PROFESSIONAL DATASHEET / MODEL SPECIFICATIONS

TX01



Min Height	**150mm / 6 in**
Max Height	**150mm / 6 in**
Closed Length	**420mm / 16.5 in**
Net Weight	**4.83kg / 10.7lbs**
Leg	**25 × 25mm**
Load Capacity	**80kg / 176.8lbs**
Packing	**1pcs**
Footprint	**830mm / 32.6 in**
Caster	**3 in**

TX02



Min Height	**150mm / 6 in**
Max Height	**150mm / 6 in**
Closed Length	**520mm / 20.5 in**
Net Weight	**4.5kg / 9.9lbs**
Leg	**25 × 25mm**
Load Capacity	**80kg / 176.8lbs**
Packing	**1pcs**
Footprint	**930mm / 36.6 in**
Caster	**3 in**

TX20



Min Height	**710mm / 28 in**
Max Height	**1470mm / 58 in**
Closed Length	**610mm / 24 in**
Net Weight	**6.9kg / 15lbs**
Sections	**3**
Tube Dia.	**25, 30, 35**
Leg	**25 × 25mm**
Load Capacity	**18kg / 39.8lbs**
Packing	**1pcs**
Footprint	**930mm / 36.6 in**
Caster	**3 in**

TX30



Min Height	**980mm / 39 in**
Max Height	**2100mm / 83 in**
Closed Length	**900mm / 35 in**
Net Weight	**6.84kg / 15.18lbs**
Sections	**3**
Tube Dia.	**25, 30, 35**
Leg	**25 × 25mm**
Load Capacity	**18kg / 39.8lbs**
Packing	**1pcs**
Footprint	**830mm / 33 in**
Caster	**3 in**

Low Roller Bases & Wheeled Riser Stands

Mobile low-position support and adjustable risers for professional lighting setups.

TX

PROFESSIONAL DATASHEET / MODEL SPECIFICATIONS

TX40



Min Height	**1170mm / 46 in**
Max Height	**2700mm / 106.3 in**
Closed Length	**1140mm / 44 in**
Net Weight	**7.88kg / 17.4lbs**
Sections	**3**
Tube Dia.	**25, 30, 45**
Leg	**25 × 25mm**
Load Capacity	**18kg / 39.8lbs**
Packing	**1pcs**
Footprint	**930mm / 36.6 in**
Caster	**3 in**

TX SERIES — Wheeled Riser Stands & Low Roller Bases

Series positioning

The FENIGAL / BTCOOPS TX Series is positioned as wheeled riser stands & low roller bases for professional purchasing programs. Low-position lighting supports and rolling risers for studios. Model-level dimensions, nominal loads and options are documented on the preceding technical pages; choose the exact SKU rather than relying on a family-wide capability claim.

Primary search keywords

low roller stand | wheeled riser stand | studio lighting base

Target B2B markets

film studio; product photography; broadcast stage

Typical buyer personas

grip rental manager; studio equipment purchaser; lighting technician

Application scenarios

Studio key/fill lighting; location video shoots; temporary indoor event illumination; trade-show fixtures when the hardware is compatible.

Balloon-light system integration

BTCOOPS balloon-light integrators may evaluate this series only after a specific fixture, mounting and wind-load review. No universal balloon-light compatibility is claimed.

Buyer qualification / quotation checklist

Request the exact model code, equipment and accessory mass, installed working height, interface dimensions, ground/site conditions, intended duty cycle and quantities. Where relevant also identify boom outreach, mobility requirements, load offset, weather and mounting accessories.

Frequently Asked Questions

How should wheeled stands be secured?

Use the approved caster lock and any required floor-stabilization procedure. Check rolling surface, cable management and loading before raising a fixture.

Can these supports carry BTCOOPS balloon lights?

Potential suitability must be assessed model by model. A balloon fixture can impose additional overturning loads; confirm the balloon diameter, complete assembled mass, center of gravity, mount interface, approved support and any wind restrictions with BTCOOPS before purchase.

Can the stand be used outdoors?

An outdoor application is possible only after a site-specific review of levelness, wind exposure, anchoring, ballast and fixture instructions. Catalog payload alone is not a wind rating.

How should buyers interpret the listed load capacity?

It is a catalog-supplied nominal load value, not an independent certification, wind-load rating or guarantee for offset/boom configurations. Request the factory rating conditions for critical applications.

What should be confirmed before an OEM or wholesale order?

Confirm the exact SKU, finish, folded dimension, transport packaging, top spigot/thread, required adapters, quantity, customization and factory-approved loading conditions.

Technical and publication notes

Specifications and product images on the preceding pages are taken from the user-provided supplier catalog. Application positioning and buyer personas are marketing recommendations; no additional test results, certifications, IP ratings, wind resistance or mounting compatibility are asserted. Confirm claims with the manufacturer before publication.

www.btcoops.com |